

Product Name **ALLSEASONS (XXX-01-H3) (XXX-01-H4)**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name CARTER HOLT HARVEY WOODPRODUCTS AUSTRALIAN GROUP OF COMPANIES
Address Level 6, Tower A, Zenith Centre, 821 Pacific Hwy, Chatswood, NSW, AUSTRALIA, 2067
Telephone 132 321
Fax 1300 362 321
Emergency 132 321
Email marketing@chhwoodproducts.com.au

Synonym(s) ALLSEASONS • CCA • F5 • F7 • IRONWOOD • OUTDOOR STRUCTURAL • RHD • ROUGHER HEADER DRY • TDAR • TREATED DAR • TREATED PINE • TREATED PINE STRUCTURAL

Use(s) INDUSTRIAL APPLICATIONS • TIMBER

MSDS Date 11 Jun 2009

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
ARSENIC	As	7440-38-2	<0.8%
CHROMIUM	Cr	7440-47-3	<0.8%
TIMBER (SOFTWOOD/HARDWOOD)	Not Available	Not Available	>98%
COPPER	Cu	7440-50-8	<0.6%

4. FIRST AID MEASURES

Eye Exposure is considered unlikely.

Inhalation Due to product form / nature of use, an inhalation hazard is not anticipated.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically

First Aid Facilities Eye wash facilities should be available.

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon/ chromium /arsenic/ copper oxides) when heated to decomposition. Dust may form explosive mixtures with air.
Fire and Explosion	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Water spray or fog, for large quantities. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt, collect and reuse where possible.
-----------------	---------------------------------------------

7. STORAGE AND HANDLING

Storage	Store in cool, dry area.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Arsenic & soluble compounds (as As)	ASCC (AUS)	--	0.05	--	--
	Chromium Metal	ASCC (AUS)	--	0.5	--	--
	Copper (fume)	ASCC (AUS)	--	0.2	--	--
	Copper, dusts & mists (as Cu)	ASCC (AUS)	--	1	--	--

Biological Limits	Ingredient	Reference	Determinant	Sampling Time	BEI
	ARSENIC	ACGIH BEI	Inorganic arsenic plus methylated metabolites in urine	End of workweek	35 mg As/L

Engineering Controls Avoid inhalation. Use in well ventilated areas. If sanding, drilling or cutting, use appropriate local extraction ventilation. Maintain dust levels below the recommended exposure standard.

PPE Wear dust-proof goggles and cotton or leather gloves. If cutting or sanding with potential for dust generation, wear: a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	GREY/GREEN COLOURED SOLID	Solubility (Water)	INSOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	NOT AVAILABLE
pH	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	COMBUSTIBLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Compatible with most commonly used materials.
Hazardous Decomposition Products	May evolve toxic gases (carbon/ chromium /arsenic/ copper oxides) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Low acute toxicity. This product may present a hazard if wood is sanded, drilled or cut with dust generation. Wood dust is classified as carcinogenic to humans (IARC Group 1), adverse health effects are usually associated with long term exposure to high dust levels. Arsenic is classified as carcinogenic to humans (IARC Group 1), however due to nature of product adverse effects are reduced. Use safe work practices to avoid generating dust.
Eye	Due to product form and nature of use, the potential for exposure is reduced. Product may only present a hazard if wood is cut or sanded with dust generation, which may result in lacrimation and irritation.
Inhalation	Due to product form and nature of use, the potential for exposure is reduced. An inhalation hazard is not anticipated unless cut, drilled or sanded with dust generation, which may result in irritation of the nose and throat. Chronic exposure to wood dust may result in result in nasal and paranasal sinus cancers (IARC Group 1).
Skin	Low irritant. Prolonged or repeated exposure to dust may result in irritation and dermatitis.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	ARSENIC (7440-38-2) Carcinogenicity: Confirmed human carcinogen (IARC Group 1) Health Surveillance: Required [NOHSC:1005(1994)] LD50 (Ingestion): 145 mg/kg (mouse) TDLo (Ingestion): 7857 mg/kg/55Y (man - gastrointestinal; skin) CHROMIUM (7440-47-3) LDLo (Ingestion): 71 mg/kg (human) TDLo (Ingestion): 1.2 mg/kg/6 weeks (rat) COPPER (7440-50-8) LD50 (Intraperitoneal): 3500 ug/kg (mouse) LDLo (Subcutaneous): 375 mg/kg (Rabbit) TDLo (Ingestion): 120 ug/kg (human - gastrointestinal upset)

12. ECOLOGICAL INFORMATION

Environment	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
--------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Dispose of to an approved landfill site. Do not burn treated timber. Contact the manufacturer for additional information.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated				
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

ARSENIC EXPOSURE: Acute arsenic ingestion generally produces symptoms within 30 to 60 minutes, but onset may be delayed for several hours if ingested with food. A metallic or garlic taste, vomiting, abdominal pain, dysphagia, and profuse watery (rice-like) and sometimes bloody diarrhoea may occur. Dehydration, intense thirst, & fluid-electrolyte disturbances are common. Hypovolemia from capillary leaking ("third spacing" of fluids) is a common early sign. Systemic arsenic poisoning from occupational exposure is uncommon. Arsenic workers have developed a hoarse voice, nasal irritation and possible perforation of the nasal septum, irritation of eyes, skin, and mucous membranes, and rarely, cirrhosis of the liver. Nausea and vomiting are infrequent. Painful ulceration of the wrist and scrotal skin, lips, and nostrils may develop with dust exposure. The primary target organs initially are the gastrointestinal tract, heart, brain, and kidneys. Eventually, the skin, bone marrow, and peripheral nervous system may be significantly damaged. The peripheral neuropathy appears similar regardless of the route of exposure.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Product Name **ALLSEASONS (XXX-01-H3) (XXX-01-H4)**

MSDS Date: 11 Jun 2009

End of Report

CHEM ALERT